

TRASFORMATORI TRIFASE

Serie T3F

Normative di riferimento CEI EN 61558-2-2

I trasformatori trifase serie T3F vengono normalmente realizzati con il collegamento delle fasi a stella e con il neutro del secondario accessibile. Su richiesta vengono eseguiti tutti i collegamenti previsti dalle normative.

La nostra produzione di serie ha le seguenti caratteristiche:

- Tensioni : 1 tensione in ingresso compresa tra 115 V. e 500 V.
1 tensione in uscita compresa tra 115 V. e 500 V.
- Classe di Isolamento : E
- Frequenza : 50 /60 HZ
- Classe di protezione : I
- Grado di protezione: IP00
- Impregnati in resina
- Tropicalizzati

THREE PHASE TRANSFORMERS

T3F Series

Standards CEI EN 61551-2-2

The transformers of T3F Series are normally built with the connection of the phases in star form and with secondary neutral accessible. On request, all connections provided for the law can be performed.

Our series production have the following details:

- Voltages : 1 input voltage between 115 V. and 500 V.
1 output voltage between 115 V. and 500 V.
- Insulation class : E
- Frequency : 50 /60 HZ
- Electrical protection class : I
- Protection index: IP00
- Impregnated
- Tropicalized



CODE CODICE	POWER POTENZA	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	WEIGHT (Kg)	CASSETTA CASE
T3F179	0,250	180	175	100	150	70	4	CASS172
T3F024	0,500	180	175	120	150	90	9	CASS172
T3F025	1	180	175	130	150	100	11	CASS172
T3F026	1,5	240	235	140	200	95	16	CASS173
T3F027	2	240	235	160	200	105	20	CASS173
T3F028	3	240	235	175	200	130	20	CASS173
T3F029	4	300	300	150	215	110	34	CASS186
T3F030	5	300	300	170	215	130	43	CASS186
T3F183	6,3	300	300	180	215	140	46	CASS186
T3F031	7,5	360	350	170	215	140	57	CASS174
T3F184	8	360	350	170	215	140	58	CASS174
T3F032	10	360	350	170	215	140	61	CASS174
T3F033	12,5	420	410	250	350	120	65	CASS174
T3F031	15	420	410	250	350	150	110	CASS175
T3F185	16	420	410	250	350	150	115	CASS175
T3F035	20	420	410	270	350	170	124	CASS175
T3F036	25	420	410	290	350	190	135	CASS176
T3F037	30	480	410	310	425	210	170	CASS176
T3F186	31,5	480	520	280	425	210	180	CASS176
T3F038	40	480	560	300	425	220	210	CASS176
T3F039	50	600	530	320	360	240	250	CASS200
T3F187	63	600	530	340	360	-	280	CASS200
T3F040	70	600	530	340	360	-	330	CASS200
T3F041	80	600	530	360	360	-	370	CASS200



T3F042	100	600	530	400	360	-	400	CASS200
T3F043	125	600	530	420	360	-	430	CASS200
T3F044	150	930	740	450	500	-	530	CASS200
T3F188	160	930	740	430	500	-	550	CASS500
T3F045	200	960	840	440	500	-	670	CASS500

